



PROVIDING INTEGRATED
WOODWORKING SOLUTIONS



ELECTRICAL AMP CONSUMPTION

H.P.	AMPS				RECOMMENDED FUSETRON			
	200V	230V	460V	575V	200V	230V	460V	575V
3/4	–	2.8	1.4	–	–	–	–	–
1	4.3	3.7	1.85	1.45	–	–	–	–
1 1/2	6.0	5.2	2.6	2.1	–	–	–	–
2	7.8	6.8	3.4	2.7	–	–	–	–
3	10.8	9.2	4.6	3.7	15	12	6 1/4	5
5	16.6	14.4	7.2	5.8	20	20	9	8
7 1/2	25.4	21.6	10.8	8.6	35	30	15	12
10	34.4	28.6	14.3	11.6	45	40	20	15
15	47.0	41.0	20.5	16.5	60	50	25	20
20	62.0	54.0	27.0	21.6	80	70	35	30
25	72.5	63.0	31.5	25.2	100	80	40	35
30	83.0	73.0	36.5	29.2	110	100	50	40
40	111.2	96	48.0	38.4	150	125	60	50
50	137.2	119.0	59.5	47.6	175	150	80	60
60	161	140.0	70	56.0	225	175	90	70
75	201.0	175.0	87.5	70.0	250	225	110	90
100	280.0	229.0	115.0	91.6	350	300	150	125
125	350.0	281.0	141.0	112.8	450	350	175	150
150	395.6	344.0	172.0	137.6	500	450	225	225
200	–	450.0	225.0	180.0	–	600	300	225